RNAV (RNP) Z RWY 19

TETERBORO (TEB)

APP CRS	Rwy Idg	6230
195°	TDZE	6
	Apt Elev	8

For uncompensated Baro-VNAV systems, procedure NA below -13°C (8°F) or above 54°C (130°F). RF required. GPS required. Missed approach requires RNP less than 1.0.

NA

MISSED APPROACH: Climb to 1500 via right turn to FOXIB, then climb to 3000 on track 306° to MORNS and hold.

D-ATIS	NEWARK APP CON	TETERBORO TOWER	GND CON	CLNC DEL	CPDLC
114.2 132.85	127.6 379.9	119.5	121.9	128.05	

Procedure NA for arrivals at COATE on T218, V116-188 northwest bound and V252 northbound.

COATE (RNP 0.30)

3000 127° (14.3)

STILLWATER STW (RNP 0.30)

3000 095° (21)

3000 095° (12)

(IAF) LELME

(IF) COMOK

2000 155° (6)

HOOTH

1500 180° (3)

(FAF) ALSIW

195° (3.8)

MSA RW19 25 NM 3000

885 944 697 559± 693 179 220 1048 774 819 335 672 449 675 499 1649 826± 849± 1806

SHOTT

3000 036° (11.1)

SOLBERG SBJ (RNP 0.30)

3000 044° (20)

MORNS

(MAP) JAPIR

061° 241° 4 NM

306° (5.9) 968

FOXIB

(9.1)

Procedure NA for arrivals on SBJ VOR/DME airway radials 028 CW 117.

ELEV 8 D TDZE 6

195°

61 98 TWR 110 6013 X 150 7000 X 150

TDZ/CL Rwys 6 and 19
REIL Rwys 1, 6, 19 and 24
HIRL Rwys 1-19 and 6-24

1500	FOXIB	3000	MORNS
		tr 306°	

COMOK 3000 155° HOOTH 2000 180° ALSIW 1500 195° JAPIR 1500

GP 3.00° TCH 54

0.7 3.8 NM 3 NM 6 NM

CATEGORY	A	B	C	D
RNP 0.10 DA	499-1¾ 493 (500-1¾)			

AUTHORIZATION REQUIRED

NE-2, 20 MAR 2025 to 17 APR 2025
NE-2, 20 MAR 2025 to 17 APR 2025