

WAAS CH 70401 W04A	APP CRS 046°	Rwy Idg TDZE 969 Apt Elev 980	6604 969 980
--	------------------------	---	---

RNAV (GPS) RWY 4

BLUE GRASS (LEX)

RNP APCH - GPS.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500, and LNAV all Cats visibility to RVR 5500.

MALSR

AS

MISSED APPROACH: Climb to 3000 direct KAYFC and hold.

ATIS 126.3	LEXINGTON APP CON 120.15 259.3 (040°-220°) 120.75 298.9 (221°-039°)	LEXINGTON TOWER 119.1 257.8	GND CON 121.9	CLNC DEL 132.35
----------------------	---	---------------------------------------	-------------------------	---------------------------

30 NM to UUKAY

135°

3000

UUKAY

225°

(IAF) UUKAY

3000 NoPT

135°

(7)

5 NM to RYYY

135°

3000

RYYY

316°

30 NM to RYYY (NoPT)

5 NM to RYYY

3100

(IF/IAF) RYYY

045°

225°

4 NM

HOLD

6000

3000

1211 A

1103 A

RW04

1078

JELID

1.5 NM to RW04

046°

2500

045°

15-21

3000 NoPT

135°

(7)

FRNZI

3100

225°

30 NM to FRNZI

316°

1623

1997

KAYFC

046°

225°

2043

FRNZI

316°

4 NM Holding Pattern

RYYY

6000

3000

225°

045°

BLAYD

2500

045°

JELID

1.5 NM to RW04

046°

2500

1480

RW04

046°

3000

KAYFC

GP 3.00°

TCH 60

5.2 NM

3.2 NM

1.5

CATEGORY	A	B	C	D
LPV DA		1169/18	200 (200-½)	
LNAV/VNAV DA		1340/35	371 (400-¾)	
LNAV MDA	1340/24	371 (400-½)	1340/35	371 (400-¾)
CIRCLING	1420-1 440 (500-1)	1440-1 460 (500-1)	1520-1½ 540 (600-½)	1600-2 620 (700-2)

ELEV 980

D

TDZE 969

4000 X 75

0.6% UP

27

700 X 150

0.5% UP

046°

TWR

1091

TDZ/CL Rwy 4

REIL Rwys 9, 22 and 27

HIRL Rwy 4-22

MIRL Rwy 9-27

SE-1, 17 APR 2025 to 15 MAY 2025

SE-1, 17 APR 2025 to 15 MAY 2025

LEXINGTON, KENTUCKY

Amdt 3A 17APR25

38°02'N-84°37'W

BLUE GRASS (LEX)

RNAV (GPS) RWY 4